Gunluk 2000-0484

IN THE CLAIMS:

1. (Currently Amended) A method carried out in a computer for provisioning rings in a ring-based network having a given topology of nodes and logical links that interconnect said nodes, and a set of traffic demands that is desired for said network to carry, comprising the steps of:

executing a process that identifies a set of feasible rings in said network, which is a subset of all possible rings in said network that satisfy a given constraint;

executing a process of identifying a routing for the traffic demands in said set of traffic demands, while aiming to that minimizes both a number of traffic demands that are not routed and an overall routing metric, where the routing metric is a cost measure that is associated with using one of said logical links in a routing path of a demand;

identifying a set of rings from among a set of feasible rings that minimizes a ring assignments cost measure that includes a cost associated with not covering routed demands with rings and a cost associated with using rings to cover demands; and

outputting the set of rings developed by said step of identifying for provisioning said nodes of said network.

- 2. (Currently Amended) The method of claim 2 1 where said constraint requires a feasible ring to have not more than a given number of nodes, and have a mileage cost that is not more than a given mileage cost.
- 3. (Original) The method of claim 1 further comprising the step of provisioning said nodes of said network in accordance with said set of rings developed by said step of identifying.
- 4. (Original) The method of claim 3 where said provisioning is accomplished through electronic transmission of information from said computer to said nodes of said network.
- 5. (Original) The method of claim 1 where said process of identifying a routing for the traffic demands

Gunluk 2000-0484

(a) considers a routing path for each of said demands, starting with the demand having a lowest routing path cost, based on a table that identifies a path having a lowest routing path cost for each arbitrary pair of nodes of said network;

HENRY BRENDZEL

- (b) assigns a demand to said path having said lowest routing path cost, if capacity exists on said path having said lowest routing path cost;
- (c) assigns said demand to a path having a higher routing path cost if capacity does not exist on said path having said lowest routing path cost; and
- (d) leaves said demand un-routed if capacity does not exist on any path that can carry said demand, thereby obtaining an identified routing of said demands.
- 6. (Original) The method of claim 1 where said process of identifying a routing for the traffic demands employs a shortest routing path metric
- 7. (Original) The method of claim 1 where said process of identifying a routing for the traffic demands identifies a set of demand routings A by:
- (a) considering a routing path for each of said demands, starting with the demand having a lowest routing path cost, based on a table that identifies a path having a lowest routing path cost for each arbitrary pair of nodes of said network;
- (b) assigning a demand to said path having said lowest routing path cost, if capacity exists on said path having said lowest routing path cost;
- (c) assigning said demand to a path having a higher routing path cost if capacity does not exist on said path having said lowest routing path cost;
- (d) leaving said demand un-routed if capacity does not exist on any path that can carry said demand, thereby obtaining a first identified routing of said demands, B;
- (e) changing order in which said demands are considered and repeating steps (b), (c), and (d) to result in a second identified routing of said demands, C; and
- (f) assigning A=B when number of un-routed demands in B is less than number of un-routed demands in C, and A=C when number of un-routed demands in B is not less than number of un-routed demands in C.
 - 8. (Original) The method of claim 7 where said table is pre-computed.

Gunluk 2000-0484

- 9. (Original) The method of claim 1 where said step of identifying a set of rings employs an integer linear programming module to obtain said set of rings that minimizes said ring assignments cost function.
 - 10. (Original) The method of claim 1 where said ring assignments cost function

is
$$\sum_{j=1}^{J} c_j x_j + p \sum_{i=1}^{J} s_i$$
, that is minimized subject to $\sum_{j=1}^{J} a_{ij} x_j \le w_i$ for each link i, and

$$\sum_{i=1}^{J} a_{ij} x_{j} + s_{i} \ge d_{i} \text{ for each link } i, \text{ where}$$

9734676589

 c_j = "cost" of a ring in candidate ring family j,

 d_i = number of units of demand routed on logical link i of said network, minus the number of available information channels that are already part of,

 $a_{ij} = 1$ if ring of family f employs link i; 0 otherwise,

 $p = \text{penalty } \underline{\text{amount supplied by a user of said method}}$ for not covering a unit of demand on a logical link[[, - one of the parameters supplied by the user to step 101]],

 w_i = number of available idle information channels on link i,

 $x_j =$ number of copies of ring family j to include in the solution, and

 $s_i =$ number of demands not covered on logical link i.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:	
☐ BLACK BORDERS	
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES	
☐ FADED TEXT OR DRAWING	
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING	
☐ SKEWED/SLANTED IMAGES	
COLOR OR BLACK AND WHITE PHOTOGRAPHS	
GRAY SCALE DOCUMENTS	
☐ LINES OR MARKS ON ORIGINAL DOCUMENT	
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY	

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.